Tesca Technologies Pvt. Ltd.



MEE 1 Order Code -22235575.4.1 CNC Lathe Machine



Salient Features

- **Single Spindle Structure**: Equipped with high-precision bearings to ensure high speed and prevent deformation due to overheating.
- **45° Slant Bed Structure**: Features a linear guideway that significantly enhances accuracy and stability.
- 8-Station Tool Turret: Increases efficiency and reduces the likelihood of malfunctions.
- Integral Motor and Guideway Design: Ensures installation accuracy and reduces errors.
- **Integral Sealed Protection**: Shields all electrical components from water, oil, and metal shavings.
- **High-Precision Collets**: Provide superior protection for the workpiece surface during machining, are durable for repeated clamping, and easy to disassemble.
- Siemens 808D Advanced Controller

Technical Specifications


- Maximum Swing Over Bed: Ø 320 mm
- Maximum Swing Over Slide: Ø 140 mm
- Maximum Machining Length with Hydraulic Chuck: 245 mm
- Spindle Type: A2-5
- Spindle Taper Hole: Ø 52 mm
- Spindle Speed Range: 60-5000 rpm
- Spindle Shift Mode: Servo
- Spindle Rated Torque: 24 Nm
- Main Motor Power: 3.7 kW

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777 India Sales: +91-9588842361 IT-2013, Ramchandrapura Industrial Area, Sitapura Extension, Jaipur-302022, India.

Follow Tescaglobal (f) (in (P)





info@tesca.in

www.tescaglobal.com



MEE 1 Order Code -22235575.4.1 CNC Lathe Machine

- Spindle Speed Maximum Power (30 min): 5.5 kW
- Chuck Type: Hydraulic Solid
- **Chuck Size:** Ø 160 mm
- Rapid Traverse Speed on X-Axis: 12 m/min
- Rapid Traverse Speed on Y-Axis: 15 m/min
- Servo Motor Torque on X-Axis: 6 Nm
- Servo Motor Torque on Y-Axis: 6 Nm
- X-Axis Travel: 170 mm
- Y-Axis Travel: 310 mm
- Guideway Type: Linear Guideway
- Turret Type: 8-Station Electric Tool Turret
- Tool Changing Time: 45° / 0.17 sec
- Turning Tool / Boring Bar Size: 20 x 20 mm / Ø 25 mm
- Hydraulic Tailstock Sleeve Diameter/Travel: Ø 65 mm / 70 mm (Hydraulic)
- Tailstock Sleeve Taper: MT-4
- Machine Weight: 1800 kg

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



CIN: U29309RJ2011PTC035213

GSTIN: 08AADCT8576E1ZZ

Export Sales: +91-9829132777 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area, Sitapura Extension, Jaipur-302022, India.

f 🔘 🎔 in 🦻

info@tesca.in

worlddidac (

www.tescaglobal.com

