



Specifications :-

- Table size - 1325×360 mm
- Table travel (X/Y/Z) - 750/320/460 mm
- Table feed(X/Y/Z) - 30~750/20~500/15~375mm/min
- Spindle taper - 7 : 24 ISO50 (H)
- Arm travel - 550mm
- Distance between spindle nose and table surface - 196-656 mm
- Distance between horizontal nose and table surface - 20-480 mm
- Distance between spindle axis and arm surface - 245mm
- Spindle speed range r.p.m - 12steps 60-1750 (V)
- T-slots(NO./width/pitch) - 3/18/80mm
- Main motor power Kw - 5.5 (H) 4 (V)
- 3 to feed Ac servo motor torque N.m - 10
- Overall size - 1800×2100×2000 mm
- Net weight - 2685 kg

(Standard accessories)

- Allen wrench : 5
- Intermediate bushing : 7:24 ISO50/MS4
- Allen wrench : 10, 14
- Fixed wrench : 13 × 17
- Fixed wrench : 22× 24
- Fixed wrench : 36 × 41
- 7:24 ISO50 milling chuck : 4\5\6\8\10\12\14\16
- Machine vise : QB160

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com



- Taper shank type milling arbor : 7:24 ISO50 Φ 32
- Milling arborm : Φ 27
- Milling arbor : Φ 32
- Draw bar : M24
- Nut : M24
- Carrier ring : 24



Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com