

**Specifications :****Table Specifications**

- **Table Size:** 1650 x 360 mm
- **T-Slot:**
 - **Number:** 5
 - **Width:** 14 mm
 - **Centre Distance:** 95 mm
- **Maximum Load of Table:** 300 kg
- **Swivel of Table:** ±35°

Machining Range

- **Table Longitudinal Travel (Manual/Auto):** 1300 mm
- **Table Cross Travel (Manual/Auto):** 300 mm
- **Table Vertical Travel (Manual/Auto):** 400 mm

Main Spindle

- **Spindle Taper:** ISO50
- **Spindle Speed / Steps:** 58-1800 RPM / 12 steps
- **Horizontal Spindle Axis to Table Surface:** 0-400 mm
- **Horizontal Spindle Axis to Arm Bottom:** 175-560 mm

Feeds

- **Feed Range:**
 - **Longitudinal:** 22-420 mm/min
 - **Cross Feed:** 22-393 mm/min

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com



- **Vertical:** 6-112 mm/min
- **Rapid Speed:**
 - **Longitudinal:** 1290 mm/min
 - **Cross Feed:** 1205 mm/min
 - **Vertical:** 400 mm/min

Power

- **Main Motor:** 4 kW
- **Feed Motor (X/Y/Z):** 1.1 kW

Standard Accessories

- Stub Arbor
- 3-Axis DRO (Digital Read Out) unit with high precision scales & fittings
- Coolant system
- Electricals
- Tool box
- Instruction manual
- Safety guard
- Spare arbor with spacer (25 mm)

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com