



Technical Specifications

Center Height	230 mm
Swing Over Bed	460 mm
Swing Over Cross Slide	270 mm
Swing in Gap	690 mm
Length of Gap	165 mm
Width of Bed	300 mm
Admits Between Centres	1000/1500/2000 mm
Spindle Nose	D1-6
Spindle Bore	58 mm
Spindle Speed	12/25-2000 rpm
Compound Rest Travel	128 mm
Cross Slide Travel	285 mm
Lead Screw Thread	6 mm / 4 TPI
Tool Shank Size	25 x 25 mm
Longitudinal Feeds	0.031-1.7 mm/rev
Cross Feeds	0.014-0.784 mm/rev
Metric Thread	41 / 0.1-14 mm
Imperial Thread	60 / 2-112 TPI
Diametrical Thread	50 / 4-112 DP
Module Thread	34 / 0.1-7 MP

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com

Tailstock Quill Diameter	60 mm
Tailstock Quill Travel	130 mm
Tailstock Quill Taper	MT-4
Main Motor Power	5.5 kW
Coolant Pump Power	0.1 kW
Overall Dimensions (L x W x H)	3250 x 1080 x 1370 mm
Net Weight	1965 kgs

Standard Accessories

- 250 mm x 3-Jaw Self-Centering Chuck (1 No.)
- 300 mm x 4-Jaw Independent Chuck (1 No.)
- Steady Rest (13-152 mm) (1 No.)
- Follow Rest (13-80 mm) (1 No.)
- Face Plate (350 mm dia) (1 No.)
- Toolbox (1 No.)
- Foot Brake (1 No.)
- Coolant System (1 No.)
- Machine Lamp (1 No.)
- Centre (1 No.)
- Centre Sleeve (1 No.)

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com