



Capacity

- Drilling Capacity: 50 mm
- Tapping Capacity: M36
- Boring Capacity: 120 mm

Drill Head

- Taper in Spindle: MT-5
- Spindle Travel: 315 mm
- Number of Spindle Speeds: 16
- Range of Spindle Speeds: 25-2000 rpm
- Number of Spindle Auto Feeds: 16
- Range of Spindle Auto Feeds: 0.04-3.20 mm/rev
- Drill Head & Column Locking: Hydraulic

Working Range

- Arm Length: 1770 mm
- Travel of Drill Head: 1250 mm
- Drilling Radius (Min./Max.): 525/1775 mm
- Distance Spindle Axis to Column: 350/1600 mm
- Distance Spindle to Base Plate: 320/1220 mm
- Diameter of Column: 350 mm

Box Table

- Box Table Size: 630 x 500 x 500 mm

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com



- Number of T-Slots in Box Table: 5
- Size of T-Slots in Box Table: 22 mm

Electrical

- Power Supply of Main Motor: 4 kW
- Power Supply of Elevating Motor: 1.5 kW

Dimension & Weight

- Overall Dimensions (L x W x H): 2500 x 1070 x 2550 mm
- Net Weight: 3500 kgs

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com