



Resistance Welding Process

- **Type:** Spot Welding, Floor Type
- **Operation:** Foot Operated Control
- **Minimum Capacity:** 15 KVA

Technical Specifications

- **Electricity Supply:**
 - AC 220/380 Volt
 - 3 Phase
 - 50 Hz
 - Fitted with ground leakage cable
- **Cooling System:** Water-cooled
- **Material Compatibility:**
 - Mild Steel, Galvanized Sheet, Stainless Steel
 - Minimum Thickness: 1.2 + 1.2 mm
- **Throat Depth:** Minimum 250 mm
- **Pressing Mechanism:** By mechanical pressing
- **Current Range:** Adjustable, with not less than 5 ranges or an equivalent system
- **Control Systems:**
 - Automatic Timing Control
 - Magnetic Control
- **Electrode Arm:**
 - Equipped with a hole for clamping the electrode holder in both vertical and sloped positions
- **Electrodes:** Minimum 3 sets (Straight, Slope, and Elbow Head)
- **Cooling System:**
 - Water receiver cooled by motor pump
 - Electrical Supply: 220 Volt, Single Phase, 50 Hz

Accessories

- Tool Box with Tools (1 Set)

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
 India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
 Sitapura Extension, Jaipur-302022, India.



info@tesca.in
 www.tescaglobal.com