



### General Specifications:

- **Type:** Monochrome Multifunctional
- **Technology:** Laser, Mono component
- **Engine Speed:** Up to 82 pages per minute (A4) / 41 pages per minute (A3)
- **Resolution:**
  - Copy/Print: 1,200 dpi quality (1,800 dpi level x 600 dpi)
  - Scan: 600 x 600 dpi, 256 greyscale
- **Warm-up Time:** 30 seconds or less from power on
- **Time to First Copy:** Approx. 2.9 seconds

### Dimensions and Weight:

- **Dimensions (W x D x H):** 680 x 811 x 1,190 mm
- **Weight:** Approx. 188 kg (including toner)

### Power Consumption:

- **Printing:** 2,000 W or less
- **Stand-by:** 630 W
- **Sleep-mode:** 10 W
- **Power Source:** AC 220 ~ 240 V, 50/60 Hz

### Noise Levels (ISO7779):

- **Printing:** 75 dB(A)
- **Stand-by:** 58 dB(A)

### Safety Standards:

- **Certifications:** TÜV/GS, CE
- **Manufactured According To:** ISO 9001 quality standard, ISO 14001 environmental standard

### Paper Handling:

- **Input Capacity:**
  - 2 x 1,500-sheet high-capacity paper feeders (60–160 g/m<sup>2</sup>, A4)
  - 2 x 500-sheet universal paper feeders (60–160 g/m<sup>2</sup>, A3–A5R, Folio)
  - 100-sheet multi-purpose tray (45–200 g/m<sup>2</sup>, A3–A6R, Folio)
- **Max. Input Capacity with Options:** 8,100 sheets (A4)

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com

- **Duplex Unit:** Double-side printing as standard (A3–A5, 64–160 g/m<sup>2</sup>)

**Processor and Memory:**

- **Processor:** Power PC750FX - 600 MHz
- **Memory:**
  - Standard: 64 MB
  - Maximum: 512 MB (2 additional DIMM slots for 32, 64, 128, 256 MB)
  - 1 CompactFlash® card slot

**Controller Language and Emulations:**

- **Controller Language:** PRESCRIBE IIe
- **Emulations:** PCL 6, KPDL3 (PostScript 3 compatible), Automatic Emulation Switching, KC GL (HP-7550A), Line Printer, IBM Proprinter X24, EPSON LQ 850, DIABLO 630

**Fonts:**

- **Outline Fonts:** 80 (PCL6)
- **PostScript KPDL 3 Fonts:** 136
- **Bitmap Font:** 1
- **Barcodes:** 45 types of one-dimensional + two-dimensional barcode (PDF-417)

**Features:**

- EMPS, Proof and hold, Private print, Job storage, Job management functionality

**Copy Specifications:**

- **Max. Original Size:** A3
- **Digital Copy Features:**
  - Energy save mode, Interrupt copy, Scan once print many, EcoPrint mode, Electronic sort, Rotate sort, Rotate copy, n-up copy, Split copy, Cover mode, Page numbering, Image overlay, Margin shift, Border erase, Positive negative, Mirror, Proof mode, Booklet copy, Program function, Job building, Job reservation, Image centring, Repeat copy, Form registration, Shared data box, Synergy print box
- **Preset Magnification Ratios:** 22 Reductions / 9 Enlargements
- **Zoom Range:** 25 - 400% in 1% steps
- **Continuous Copy:** 1 - 9,999
- **Memory Capacity:** Standard 128 MB and 40 GB HDD

**Scan Specifications:**

- **Bundled Software:** DB-Assistant, Scanner file utility, Address Book, Address Editor, TWAIN source
- **File Types:** TIFF, PDF (high compressive/encrypted)
- **Original Recognition:** Text, Photo, Text + Photo, OCR
- **Max. Scan Size:** A3
- **Scan Functionalities:** Scan-to-PC, Scan-to-email, Network TWAIN, Scan-to-SMB
- **Scan Resolution:** 600, 400, 300, 200 dpi
- **Scan Speed:** 110 originals per minute (300 dpi/A4 Duplex)

**Interfaces:**

- **Standard Interfaces:** Slot for optional CompactFlash®-Card, USB 2.0 (Hi-Speed), High-speed bi-directional parallel (IEEE 1284), Fast Ethernet (10/100BaseTX), KUIO-LV interface slot

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com