

Refrigeration Trainer allows students & industry professionals to learn the fundamentals of Simple Vapour Compression Refrigeration System. The design of this Refrigeration Training System is to allow the user to study this Technology in great detail. The training system introduces various sub-systems with real components.

The training system brings a comprehensive view of the entire Refrigeration system. Actual component study and their interconnection, functions, operation, diagnosis, etc. are a part of the scope of training.

The construction of the trainer is on a main platform unit mounted on a trolley. This helps the students to place the trainer at their desired position. However, the height of the trainer is as such, the students can comfortably observe the reading while performing the experiments. The unit is opened, in order to provide an open exposure to the students for understanding the importance of each component in the process cycle.

In this trainer, students can learn how to calculate the Coefficient of Performance (C.O.P.) of a compressor, based on which he / she can know the capacity of a compressor. Apart from this, students are also able to know the power consumed by the compressor.

The front panel also includes Toggle Switches, LCD, Pressure Dials, Voltmeter and Ammeter.

- Refrigerant (R134) used is non-poisonous, harmless to body and eco-friendly
- Compact and Self-contained
- Mounted on trolley for mobility
- Digital LCD for Temperature
- Multi point temperature measurement
- Process Diagram on front panel
- Easy component identification

Technical Specifications

: 10112Turns		
: 230 V AC – 50 Hz,	VAC, 800 L/H	
0.40 Amps, 9 watt	Heater : 220 VAC, 50 Hz,	500 watt
and 1360 RPM	Rotameter : 0 to 30 LPM, Acr	ylic body
: Capacity: 20 litres	LCD : 16' 2	
: 1/3 HP, 925 BTU,	Temperature Range : 0°-100°C	
150 watt, R134a	1 0	
(Refrigerant), 220	Scope of Learning	
VAC-50 Hz,	• To study the Simple Veneur Commenceion Define	anotion Swatam
: 1/4- Threaded		eration System
(male)	(SVCR)	
: 0-300 PSIG & 0-	• To calculate the Co-efficient of Performance (C.O.P)	
21 kg/cm2	• To calculate the power consumption of the compressor	
: -30 to 150 PSIG		
: 0 to 5 Amps AC		
: 0 to 300 VAC		
: Submersible, 220		
	 10 11 2 tunis 230 V AC - 50 Hz, 0.40 Amps, 9 watt and 1360 RPM Capacity : 20 litres 1/3 HP, 925 BTU, 150 watt, R134a (Refrigerant), 220 VAC - 50 Hz, 1/4 - Threaded (male) 0 - 300 PSIG & 0 - 21 kg/cm2 -30 to 150 PSIG 0 to 5 AmpsAC 0 to 300 VAC 	: $230 \text{ VAC} - 50 \text{ Hz}$, $0.40 \text{ Amps}, 9 \text{ watt}$ and 1360 RPM VAC, 800 L/H : $220 \text{ VAC}, 50 \text{ Hz}$, Rotameter: $220 \text{ VAC}, 50 \text{ Hz}$, $1.50 \text{ watt}, R134a$ (Refrigerant), 220 VAC - 50 Hz,: $0 \text{ to } 30 \text{ LPM}, \text{Acr}$ ICD: $0 \text{ to } 30 \text{ LPM}, \text{Acr}$:1/3 HP, 925 BTU, 150 watt, R134a (Refrigerant), 220 VAC - 50 Hz,:IcCD: $16' \text{ 2}$ Temperature Range: $0^{\circ} - 100^{\circ}\text{C}$: $1/4 - \text{ Threaded}$ (male):To study the Simple Vapour Compression Refrige (SVCR).: $0 - 300 \text{ PSIG } \& 0 - 21 \text{ kg/cm2}$:To calculate the Co-efficient of Performance (C.O.P):: $0 \text{ to } 300 \text{ VAC}$.

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension, Jaipur-302022, Rajasthan, India, Mob./Whatsapp: +91-9829132777; Email: info@tesca.in, Website: www.tescaglobal.com



