



EFFLUENT TREATMENT PLANT

FOR TWO WHEELER WASHING SEGMENT

EFFLUENT TREATMENT PLANT

FOR TWO WHEELER SEGMENT



Technical Specification

Electrical	: 230 V (\pm 20%), 50 hz, Single Phase
Flow rate	: 1000 lpm
Suction tubing	: 4/6 mm
Discharge tubing	: 4/6 mm
Dosing rate	: 6 mph at 4 kg/cm ²
Strokes / minute	: Max:400 Min:50
Fuse	: 600 mA
Level switch interlock	: Normally open
Relay output	: Normally open. Closes in case the pump stops for any reason

About ETP

ATS ELGI ETP plays a significant role in the treatment of vehicle washing waste water. Organic matter, inorganic matter, heavy metals, oil & grease, suspended particles and other contaminants are treated in the waste water treatment process of an ETP plant.

Scope of Supply

- Sand Bed filter,
- Activated carbon filter
- Pre filter & Fine filter
- Mono block pump 1 No.
- Dosing pump 1 No.
- Control Panel
- Pressure Gauge

Advantages




**COMPACT
UNIT**



**NO MAJOR CIVIL WORK
REQUIRED**



**USER
FRIENDLY**



**PLUG & PLAY
OPERATION**



**MAINTAINS STATUTORY
NORMS**