

**Specification:**

- CRT : 6 "rectangular screen with internal graticule, 8×10div
- Bandwidth : 20MHz
- **Vertical deflection**
 - Display model : CH1,CH2,ADD, ALT, CHOP
 - Deflection factor : 5mV/div to 5V/div ±3%, 1mV/div to 1V/div ± 5%(x5), 10steps
 - Rise time : ≤17.2ns
 - Max. input voltage : 250V(DC+AC peak) ≤1KHz
 - Input Coupling : AC,DC,GND
 - Polarity selection : +or-(CH2 Only)
- **Horizontal deflection**
 - Display mode : 1,10,X-Y
 - Time base : 0.2μs/div to 0.2s/div,9 ranges
 - Sweep magnification : ×10
 - Accuracy : ±3%
- **Trigger system**
 - Trigger mode : NORM, AUTO, TV-V,TV-H
 - Trigger source : CH1,CH2, VERT,LINE,EXT
 - Sensitivity and frequency : 20Hz-20MHz(VERT)
 - ➔ AUTO, NORM : 0.5div (INT), 0.5Vp-p(EXT)
 - ➔ TV-V,TV-H : At least 1 div or 1Vp-p
 - Input impedance : 1MΩ
- **X-Y operation (X-Y)**
 - X-Y phase difference (X-Y) : ≤3°,DC-50kHz
- **Others**
 - Calibration waveform : Frequency: 1KHz ± 20%, Voltage:0.5V ± 10%
 - Power supply : 220V/110V ± 10%;50/60Hz
 - Dimensions : 310(W) ×130(H) ×370(D)mm
 - Weight : 8.5KG

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com