

**Specifications:**

- It's an innovated accurate, shock-proof handheld instrument with robust protective holster alongside and the adjustable back tilt device with hook-up design. It can offer accurate, reliable, True-RMS measurements with high quality Band movement, double-sided glass-epoxy PCB & unique-designed circuit, as well as mirrored Aluminum dial plate etc. It has the perfect full overload & mis-used protection via two Fuses, Oxide Varactor & Diodes.
- Power ON Light Indicator with Auto Power Off
- Heavy ABS housing plus compact protective holster alongside
- High input impedance 10Mohm/DCV/ACV
- Certificates with CE-EMC & LVD CAT II 1000V, CAT III 500V, & EK1
- High Quality -Band Movement built-in
- True RMS readings for ACV/ACA testing
- ACV/DCV test ranges:0.05-0.5-2.5-10-50-250-1000V with accuracy <3% of F.S.
- Resistance test Ranges: x1, x10, x100, x1K, X10K, X100K,X1M (2000MΩ Max.) with accuracy <3% of Arc.
- Capacitance test Ranges: 0.0025-0.25-25uF with accuracy <3% of F.S. via CT-1;
- 2 ~ 2, 000 uF approximate value ( With Extra Kit)
- Other Tests including Dry Battery, Continuity Buzzer, Decibel, Diode, Transistor hFE etc.
- Frequency : 0.25-2.5K-25K Hz. with accuracy <3% of F.S
- Dimensions & Unit Weight: 160(L) x 105(W) x 40(H) mm & 430g

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777  
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,  
Sitapura Extension, Jaipur-302022, India.



info@tesca.in  
www.tescaglobal.com