



Features:

- Over voltage/current audible alarm
- High voltage warning
- Auto power off (can be disabled)
- Low power consumption
- Fast and accurate capacitance measurement
- 2m drop proof

Specifications:

- DC voltage (V): 600mV/6000mV/60V/600V, $\pm(0.5\% + 3)$
- AC voltage (V): 600V, $\pm(1.2\% + 3)$
- DC current (A): 600uA/60mA/600mA/10A, $\pm(1\% + 2)$
- AC DC current (A) : 10A
- Resistance (Ω): 600 Ω /6000 Ω /60k Ω /600k Ω /60M Ω , $\pm(0.8\% + 2)$
- Capacitance (F): 9.999nF/99.99nF/999.9nF/9.999 μ F/99.99 μ F/999.9 μ F/9.999mF, $\pm (4\% + 5)$
- Display count: 6000
- Range selection: Manual
- Diode: yes
- Continuity buzzer: Yes
- NCV: Yes
- LCD backlight: yes
- Test probe holder: yes
- Data hold: yes
- Low battery indication: yes
- Overload indication: yes
- Power: 1.5V battery (R03) x 2
- Display: 56.8mm x 36.1mm
- Net weight: Approx. 255g (with batteries)
- Dimension: Approx. 155mm x 76.5mm x 49mm
- Standard accessories: English Manual

Note: Specifications are subject to change, Photos shown above are Indicative, Actual Product can Vary.



Export Sales: +91-9829132777
India Sales: +91-9588842361



IT-2013, Ramchandrapura Industrial Area,
Sitapura Extension, Jaipur-302022, India.



info@tesca.in
www.tescaglobal.com